

Pos	Qty	Art.Code	Description		DIN	Model	Material
1	1	55-700-188-GG	Motor housing	mh240	-	1946	GG 25
3	1	55-702-271-BE	Stator with thermo switches	20 kW-2	-	020-2135160J	
4	1	55-703-364-RM	Rotor	20 kW-2	-	030-3135160J	AlSi 431
5	1	55-750-107	Ball bearing	6308 RS1/ C3 GJN	-		
6	1	55-750-116	Ball bearing	6311-2Z	-		
10	1	55-704-153-GG	Seal housing		-	1950	GG 25
11	1	55-704-156-NI	Membrane	RW/RT60	-		NBR
12	1	55-706-301	Mechanical seal	Ø50	-		Carb/ceramic/N
13	1	55-706-300	Mechanical seal	Ø50	-		SiC/ceramic/NB
15	1	55-707-186-GG	Bearing housing	Ø120	-	2094	GG 25
16	1	55-707-179-GG	Bearing housing cover		-	2062	GG 25
17	1	55-707-177-GG	Bearing housing cover		-	2035	GG 25
20	1	55-709-321-GG	Connection box	3x G7/8"	-	2095	GG 25
56	1	55-713-210-RZ	Data plate	Robot Pumps	-		AISI 316
59	1	55-751-120	O-ring	90x 3.00	-		NBR
60	1	55-751-018	O-ring	120.24x 3.53	-		NBR
61	1	55-751-151	O-ring	297.8x 6.99	-		NBR
62	1	55-751-169	O-ring	280x 5.00	-		NBR
63	1	55-751-200	O-ring	125x 4.00	-		NBR
66	1	55-752-005	Circlip	A 40x1.75	471		spring steel
67	1	55-752-011	Circlip	A 55x2	471		spring steel
68	1	55-752-006	Circlip	A 50x2	471		spring steel
70	1	55-753-025	Stud bolt	M 8x 12	939		AISI 304
71.1	1	55-754-028	Hexagon socket screw	M 8x 16	912		AISI 304
71.2	1	55-754-028	Hexagon socket screw	M 8x 16	912		AISI 304
73	2	55-754-092	Hexagon socket screw	M10x 20	912		AISI 304
73	1	55-709-060	Plug	M20x 1 1/2	-		CuZn 40
74	8	55-754-029	Hexagon socket screw	M 8x 25	912		AISI 304
75	4	55-754-099	Hexagon socket screw	M12x 30	912		AISI 304
76	4	55-754-201	Hexagon socket screw	M10x 80	912		AISI 304
77	4	55-754-092	Hexagon socket screw	M10x 20	912		AISI 304
78	6	55-754-027	Hexagon socket screw	M10x 25	912		AISI 304
79	(4)	55-756-045	Grub screw	M12x16	916a		AISI 304
81	1	55-755-028	Nut	M 8	934		AISI 304
83	1	55-756-125	Key	10x 8x30	6885A		AISI 316
84.1	1	55-756-028	Dubo ring	M 8 type 303	-		PA 6.6
84.2	1	55-756-028	Dubo ring	M 8 type 303	-		PA 6.6
85	2	55-756-027	Dubo ring	M10 type 305	-		PA 6.6
85	1	55-713-181	Seal ring	A 20x24x1.5	-		Cu
87	8	55-757-076	Data plate rivet	2.9x6.5	-		AISI 316
89	1	55-758-077	Lock washer	(M 8)	127a		AISI 304
90	4	55-758-074	Lock washer	(M12)	127a		AISI 304
94	1	55-759-070	Cable lug	M 8 (16mm2)	-		
95	1	55-906-068	Hose clamp	110-130 mm	-		RVS
96	1	55-906-069	Oil	Marcol 152	-		
101	1	55-701-207-GG	Pump casing	RW6130/4032	-	2100	GG 25
118	1	55-751-014	O-ring	259.7x 6.99	-		NBR
124	4	55-754-081	Hexagon socket screw	M12x 80	912		AISI 304
124	1	55-756-045	Grub screw	M12x16	916a		AISI 304
140	1	55-708-358-NG	Impeller	252 RW/BW60/6132	-	1917	GGG 40
141	1	55-713-160-RZ	Impeller hubcap	Ø44x13.5x8	-		AISI 316
145	1	55-754-180	Hex. sock. screw counter sun	M12x 40	7991		AISI 316

Supplement transportation bracket installation -F, T and V

222	1	55-710-480-ST	Transportation bracket	RT60/ RW61, kleine kabel	-		Fe 360
223	2	55-754-099	Hexagon socket screw	M12x 30	912		AISI 304

Supplement installation -F

200	1	55-710-317-NG	Suspension bracket	V mh240	-	1964	GGG 40
201	4	55-754-111	Hexagon socket screw	M12x 40	912		AISI 304
203	1	55-912-062	Shackle	16mm	-		AISI 316
210	1	55-712-143-GG	Hose connection	4"-90gr.	-	1788	GG 25
210	(1)	55-712-144-GG	Hose connection	4"-3-90gr.	-	1789	GG 25
210	(1)	55-712-183-GG	Hose connection	4"-90gr. (SL)	-	2091	GG 25
210	(1)	55-712-170-st	Thread connection	G 4"-90gr.Bu	-		Fe galv.
210	(1)	55-712-194-st	Thread connection	NPT 4"-90gr.Bu	-		Fe 360
211	4	55-753-152	Hexagon-head bolt	M12x 50	931		AISI 304
211	(4)	55-753-158	Stud bolt	M12x 35	939		AISI 316
213	4	55-755-083	Nut	M12	934		AISI 304

Pos	Qty	Art.Code	Description		DIN	Model	Material
214	4	55-758-095	Washer	(M12)	125		AISI 304
218	1	55-761-002	Gasket	Ø140xØ105x2	-		CR
230	1	55-715-066-ST	Support ring	W20/40/60-Ø100	-		Fe galv.
231	3	55-754-079	Hexagon socket screw	M10x 30	912		AISI 304

Supplement installation -H

200	1	55-710-381-ST	Suspension bracket	H-60	-		Fe galv.
201	2	55-754-099	Hexagon socket screw	M12x 30	912		AISI 304
201	2	55-754-088	Hexagon socket screw	M16x 40	912		AISI 304
201	2	55-755-086	Nut	M16	934		AISI 304
203	1	55-912-062	Shackle	16mm	-		AISI 316
210	1	55-712-053-GG	Hose connection	4"	-	1293	GG 25
211	4	55-753-152	Hexagon-head bolt	M12x 50	931		AISI 304
213	4	55-755-083	Nut	M12	934		AISI 304
214	4	55-758-095	Washer	(M12)	125		AISI 304
218	1	55-761-002	Gasket	Ø140xØ105x2	-		CR
220	1	55-712-131-GG	Suction elbow	4"	-	1467A	GG 25
221	3	55-754-027	Hexagon socket screw	M10x 25	912		AISI 304

Supplement installation -V

200	1	55-710-317-NG	Suspension bracket	V mh240	-	1964	GGG 40
201	4	55-754-111	Hexagon socket screw	M12x 40	912		AISI 304
203	1	55-912-062	Shackle	16mm	-		AISI 316
211	4	55-753-152	Hexagon-head bolt	M12x 50	931		AISI 304
213	4	55-755-083	Nut	M12	934		AISI 304
214	4	55-758-095	Washer	(M12)	125		AISI 304
218	1	55-761-002	Gasket	Ø140xØ105x2	-		CR
218	(1)	55-761-057	Gasket	Ø150xØ 97x2	-		CR

Auxiliary cable

35	1	55-709-147	Cable	4x2.5mm ² Ø13.0- Ø15.0	-		Ozoflex
36	1	55-709-016-RZ	Cable entry	G 7/8"	-	2221	AISI 316
38	1	55-709-028	Cable sleeve	27.5x14x23	-		CR
39	2	55-709-125	Pressing ring	27.5x15x4	-		CuZn 40
48	3	55-759-021	Cable connector	(2.5mm ²)	-		

Cable list YD 380V 50Hz

35	2	55-709-148	Cable	4x4mm ² Ø15.1- Ø17.0	-		Ozoflex
36	2	55-709-002-RZ	Cable entry	G 7/8"	-	2209A	AISI 316
37	2	55-709-004-RZ	Clamp	Ø15-17	-	2210	AISI 316
38	2	55-709-029	Cable sleeve	27.5x16x23	-		CR
39	4	55-709-167	Pressing ring	27.5x18x4	-		CuZn 40
45	4	55-754-093	Hexagon socket screw	M 6x 16	912		AISI 304
48	6	55-759-075	Cable connector	(4-6mm ²)	-		

Cable list YD 415V 50Hz

35	1	55-709-151	Cable	SUBCAB 7G2.5mm ²	-		CR / EPR / Cu
36	1	55-709-002-RZ	Cable entry	G 7/8"	-	2209A	AISI 316
37	1	55-709-005-RZ	Clamp	Ø18-21	-	2211	AISI 316
38	1	55-709-166	Cable sleeve	27.5x18x23	-		CR
39	2	55-709-167	Pressing ring	27.5x18x4	-		CuZn 40
45	2	55-754-093	Hexagon socket screw	M 6x 16	912		AISI 304
48	6	55-759-007	Cable connector	(2.5mm ²)	-		

Option Sparepart kit

600	1	55-520-1001		RW/RD60	-		
-----	---	-------------	--	---------	---	--	--

Option: rotorshaft with AISI 316 shaftend

Pos	Qty	Art.Code	Description		DIN	Model	Material
4	1	55-703-364-RZ	Rotor	20 kW-2	-	030-3135160J	AISI 431/AISI 3

Optional viton seals

13	1	55-706-324	Mechanical seal	Ø50	-		SiC/ceramic/FP
84	1	55-756-127	Seal ring	(M 8)	-		PTFE
85	2	55-756-128	Seal ring	(M10)	-		PTFE
63	1	55-751-223	O-ring	125.0x 4.0	-		FPM
61	1	55-751-224	O-ring	297.8x 6.99	-		FPM
62	1	55-751-225	O-ring	280x 5.00	-		FPM
118	1	55-751-183	O-ring	272x 7.00	-		FPM
218	1	55-761-060	Gasket	Ø140xØ105x2	-		FPM

Option: impeller in special material

140	(1)	55-708-358-RZ	Impeller	252 RW/BW60/6132	-	1917	AISI 316
140	(1)	55-708-358-RU	Impeller	252 RW/BW60/6132	-	1917	AISI 329

Option: waterdetector


15	1	55-707-186-GG	Bearing housing	Ø120	-	2094	GG 25
32	1	55-756-144	Plug	M16x 1 1/2	910		CuZn 40
32	1	55-717-087	Plug	M15x 1 1/2	7604		
300	1	55-717-031	Line bushing	M15x 1 1/2	-		
300	1	55-717-122	Water detector	M16x1.5	-		
301	1	55-717-068	Detector		-		
303	1	55-759-083	Wire clamp	(2.5mm2)	-		
306	1	55-759-105	Contact lip	(2.5mm2)	-		

Option: zincanode

500	1	55-717-071	Anode	Ø 100	-		Zn
501	3	55-717-115	Distance tube	Ø 20x Ø 10 l=12mm	-		AISI 304
502	(3)	55-754-027	Hexagon socket screw	M10x 25	912		AISI 304
231	(3)	55-754-116	Hexagon socket screw	M10x 35	912		AISI 304

Parts list drawing

Option: waterdetector



Parts list drawing

